

INVEREX

Nitrox 6kW Hybrid Inverter



DATASHEET / SPECIFICATIONS

NAME	DETAIL	NAME	DETAIL
Brand	Inverex	Max. Efficiency	97.6%
Model	Nitrox Hybrid 6kW SP-48V	Solar Charger	140 Ampere
Solar Supports	7800 watt	Output Frequency	50/60Hz
Rated PV Input Voltage	370 (125~500)	Battery Voltage Range	40~60 volt
MPPT Voltage Range	150-425 volt	Max. Charging Current	135 Ampere
PV Input Current	13+13 Ampere	Charging Curve	3 Stages
Number of MPPT	2	Transfer Time	4ms
Strings Per MPPT	1+1	Cooling	Smart Cooling
Phase	Single	Noise	<30 dB
WIFI	Yes	Dimensions	17x13x9.4 inches (HxWxD)
Dual Output	Yes	Installation Style	Wall-mounted
Support Generator Connection	Yes	Warranty	5 Years

For Price & More Info. Visit:



WWW.PRICECITY.COM.PK

Scan
QR



*Disclaimer at website.

INVEREX

Nitrox 6kW Hybrid Inverter FEATURES

- Zero Export
- 5 Years Warranty, Dual MPPT
- Can be installed 7800 watts of panels
- IP65 Ingress Protection
- WiFi Monitoring, 48-volt system
- Internal SPD, High Surge Endurance
- Can work without batteries
- Maximum Efficiency 97.6%
- Supports Panels up to 600 watt
- Pure sine wave inverter, RS485/RS232
- Compatible with mains voltage and generator power.
- Hybrid Model, Different Protection
- On-Grid (Grid feeding option is available)
- Touchscreen Display
- High DC voltage Range



 135 AMP
Solar Charger

For Price & More Info. Visit:



Scan
QR



WWW.PRICECITY.COM.PK

*Disclaimer at website.