

AKCOME

730 watt HJT Solar Panel

DATASHEET / SPECIFICATIONS



NAME	DETAIL	NAME	DETAIL
Brand	AKCOME	Tier Quality	Tier 1
Panel Wattage	730 watt	Fire Rating	UL Type 2, IEC Class C
Cell Type	B-type, Mono Perc Half Cut 132	Glass	3.2mm tempered glass
1st Year Power Degradation	< 1%	Number of cells	132
Module Efficiency	23.5%	Power Output Tolerance	IP68, 3 Bypass Diodes
Open Circuit Voltage	50.37 volt	Cable	4mm ²
Short Circuit Current	18.3 Ampere	Power Output Tolerance	0~+5W
Bifacial	Yes	Weight	38.5 kg
Operating Temperature	-40°C ~ +85°C	Height	93.85 inches
Class	A	Width	51.3 inches
Max. Power Current	18.3 Ampere	Depth	1.3 inches
Temperature Coefficient of Isc	+0.048%/°C	Warranty	15 Years (Material), 30 Years (Performance)

For Price & More Info. Visit:



WWW.PRICECITY.COM.PK

Scan
QR



*Disclaimer at website.

AKCOME

730 watt Solar Panel

FEATURES

- Module efficiency up to 23.5%
- Strong durability
- Good spectral response
- Good transparency
- Low cost
- High bifacial gain
- Power generation per watt increased by 3.4%
- Tier-1 quality
- Thin wafer
- Low-temperature coefficient
- Class-A application classification
- 30 Years performance warranty



For Price & More Info. Visit:



Scan
QR



WWW.PRICECITY.COM.PK

*Disclaimer at website.